


CARTRIDGE

22-250 Remington A.I. 40 grain

Version 8.0

Nosler®

UP FRONT



22-250 Remington A.I. 40 grain

22 Cal. (.224")

MAXIMUM O.A.C.L. 2.350"

TESTED O.A.C.L.

B.C.

S.D.

| | | | | |
|--------------------------|-----------------|--------|-------|-------|
| Ballistic Tip® | 40gr. Spitzer | 2.350" | 0.221 | 0.114 |
| Ballistic Tip® Lead Free | 40gr. Spitzer | 2.350" | 0.220 | 0.114 |
| Varmageddon® | 40gr. FBHP | 2.280" | 0.158 | 0.114 |
| Varmageddon® | 40gr. FB Tipped | 2.350" | 0.211 | 0.114 |

| | | | |
|-------------|----------------|--------------------|------------|
| CASE TYPE: | Nosler | PRIMER TYPE | Rem 9 1/2 |
| CASE HOLDS: | 48.0 Gr. WATER | BARREL Length/Make | 26" Shilen |
| | | BARREL Twist | 1-14" |

| POWDER TYPE | POWDER CHG. GRS. | MUZZLE VEL. F.P.S. | LOAD DENSITY (VOLUME) |
|------------------------------------------------|------------------|--------------------|-----------------------|
| IMR 4895 | 41.0 * MAX. | 4124 | 94% |
| | 39.0 | 3883 | 89% |
| | 37.0 | 3642 | 85% |
| H380 | 46.5 MAX. | 4129 | ** 102% |
| | 44.5 | 3955 | 98% |
| | 42.5 * | 3781 | 93% |
| RL15 | 41.5 MAX. | 4181 | 90% |
| | 39.5 * | 4013 | 86% |
| | 37.5 | 3763 | 81% |
| Viht N135 | 39.5 MAX. | 4199 | 96% |
| | 37.5 | 4003 | 91% |
| | 35.5 * | 3806 | 86% |
| Big Game | 44.0 MAX. | 4206 | 96% |
| | 42.0 * | 4023 | 92% |
| | 40.0 | 3826 | 88% |
| Varget | 41.0 MAX. | 4209 | 92% |
| | 39.0 | 4007 | 88% |
| | 37.0 * | 3800 | 83% |
| Viht N140 | 40.0 MAX. | 4209 | 97% |
| | 38.0 * | 4009 | 92% |
| | 36.0 | 3840 | 87% |
| W748 | 42.0 * MAX. | 4217 | 91% |
| | 40.0 | 4053 | 87% |
| | 38.0 | 3888 | 82% |
| IMR 4064 | 40.0 * MAX. | 4298 | 92% |
| | 38.0 | 4067 | 87% |
| | 36.0 | 3833 | 82% |
| IMR 3031 Most Accurate Powder Tested | 38.5 MAX. | 4338 | 91% |
| | 36.5 * | 4093 | 86% |
| | 34.5 | 3869 | 81% |

All cartridge measurements are SAAMI maximum and due to variations from manufacturers actual measurements may vary
 * Because Nosler, Inc. has no control over the actual components selected, the manner in which they are assembled or the condition of the firearm used, no responsibility, either expressed or implied is assumed for the use of this data.
 In no event shall Nosler, Inc. be liable for any damages resulting from the use of this data.

* = Most accurate load tested

** = Compressed load