


CARTRIDGE

44 Remington Magnum (Rifle) 240 grain

Version 8.0

Nosler®

UP FRONT



44 Remington Mag (Rifle) 240 grain

44 Cal. (.429")

MAXIMUM S.A.A.M.I. O.A.C.L. 1.610"

TESTED O.A.C.L.

B.C.

S.D.

| | | | | |
|-------------------|-----------|--------|-------|-------|
| Sporting Handgun™ | 240gr JHP | 1.580" | 0.173 | 0.186 |
| Sporting Handgun™ | 240gr JSP | 1.580" | 0.177 | 0.186 |

| | | | |
|-------------|----------------|--------------------|-------------|
| CASE TYPE: | Winchester | PRIMER TYPE | WLP |
| CASE HOLDS: | 22.4 Gr. WATER | BARREL Length/Make | 18.5" Ruger |
| | | BARREL Twist | 1-38" |

| POWDER TYPE | POWDER CHG. GRS. | MUZZLE VEL. F.P.S. | LOAD DENSITY (VOLUME) |
|--------------------------------------------|------------------|--------------------|-----------------------|
| A #5 | 13.4 MAX. | 1370 | 63% |
| | 12.9 | 1324 | 61% |
| | 12.4 * | 1279 | 58% |
| 800X | 12.6 * MAX. | 1398 | 90% |
| | 12.1 | 1356 | 86% |
| | 11.6 | 1317 | 83% |
| H57 | 15.5 MAX. | 1466 | 77% |
| | 15.0 | 1423 | 74% |
| | 14.5 * | 1380 | 72% |
| Blue Dot | 15.0 MAX. | 1477 | 86% |
| | 14.5 | 1432 | 83% |
| | 14.0 * | 1398 | 80% |
| W296 | 23.8 MAX. | 1723 | ** 108% |
| | 23.3 | 1688 | ** 106% |
| | 22.8 * | 1642 | ** 104% |
| H110 Most Accurate Powder Tested | 23.8 MAX. | 1724 | ** 108% |
| | 23.3 | 1697 | ** 106% |
| | 22.8 * | 1661 | ** 103% |

All cartridge measurements are SAAMI maximum and due to variations from manufacturers actual measurements may vary

* Because Nosler, Inc. has no control over the actual components selected, the manner in which they are assembled or the condition of the firearm used, no responsibility, either expressed or implied is assumed for the use of this data.

In no event shall Nosler, Inc. be liable for any damages resulting from the use of this data.*

* = Most accurate load tested

** = Compressed load


CARTRIDGE

44 Remington Magnum (Rifle) 240 grain

Version 8.0

Nosler[®]

UP FRONT



44 Remington Mag (Rifle) 240 grain 44 Cal. (.429")

MAXIMUM S.A.A.M.I. O.A.C.L. 1.610"

TESTED O.A.C.L.

B.C.

S.D.

| | | | | |
|-------------------|-----------|--------|-------|-------|
| Sporting Handgun™ | 240gr JHP | 1.580" | 0.173 | 0.186 |
| Sporting Handgun™ | 240gr JSP | 1.580" | 0.177 | 0.186 |

| | | | |
|-------------|----------------|--------------------|-------------|
| CASE TYPE: | Winchester | PRIMER TYPE | WLP |
| CASE HOLDS: | 22.4 Gr. WATER | BARREL Length/Make | 18.5" Ruger |
| | | BARREL Twist | 1-38" |

| POWDER TYPE | POWDER CHG. GRS. | MUZZLE VEL. F.P.S. | LOAD DENSITY (VOLUME) |
|--------------------------------------------|------------------|--------------------|-----------------------|
| A #5 | 13.4 MAX. | 1370 | 63% |
| | 12.9 | 1324 | 61% |
| | 12.4 * | 1279 | 58% |
| 800X | 12.6 * MAX. | 1398 | 90% |
| | 12.1 | 1356 | 86% |
| | 11.6 | 1317 | 83% |
| H57 | 15.5 MAX. | 1466 | 77% |
| | 15.0 | 1423 | 74% |
| | 14.5 * | 1380 | 72% |
| Blue Dot | 15.0 MAX. | 1477 | 86% |
| | 14.5 | 1432 | 83% |
| | 14.0 * | 1398 | 80% |
| W296 | 23.8 MAX. | 1723 | ** 108% |
| | 23.3 | 1688 | ** 106% |
| | 22.8 * | 1642 | ** 104% |
| H110 Most Accurate Powder Tested | 23.8 MAX. | 1724 | ** 108% |
| | 23.3 | 1697 | ** 106% |
| | 22.8 * | 1661 | ** 103% |

All cartridge measurements are SAAMI maximum and due to variations from manufacturers actual measurements may vary
 * Because Nosler, Inc. has no control over the actual components selected, the manner in which they are assembled or the condition of the firearm used, no responsibility, either expressed or implied is assumed for the use of this data.
 In no event shall Nosler, Inc. be liable for any damages resulting from the use of this data.*

* = Most accurate load tested

** = Compressed load