


# CARTRIDGE

## 44 Remington Magnum (Rifle) 300 grain

Version 8.0

# Nosler<sup>®</sup>

## UP FRONT



## 44 Remington Mag (Rifle) 300 grain 44 Cal. (.429")

**MAXIMUM S.A.A.M.I. O.A.C.L. 1.610"**

**TESTED O.A.C.L.**

**B.C.**

**S.D.**

Sporting Handgun™	300gr JHP	1.580"	0.206	0.233
CASE TYPE:	Winchester	PRIMER TYPE	WLP	
CASE HOLDS:	17.6 Gr. WATER	BARREL Length/Make	18.5" Ruger	
		BARREL Twist	1-38"	

POWDER TYPE	POWDER CHG. GRS.	MUZZLE VEL. F.P.S.	LOAD DENSITY (VOLUME)
<b>Viht 3N37</b>	11.0 * MAX.	1183	98%
	10.5	1129	93%
	10.0	1075	89%
<b>A #9</b> Most Accurate Powder Tested	18.0 * MAX.	1379	** 109%
	17.5	1337	** 106%
	17.0	1295	** 103%
<b>A #7</b>	15.0 * MAX.	1382	87%
	14.5	1338	84%
	14.0	1294	81%
<b>2400</b>	17.0 MAX.	1481	** 112%
	16.5	1433	** 109%
	16.0 *	1385	** 106%
<b>W296</b>	21.0 MAX.	1507	** 122%
	20.5	1474	** 119%
	20.0 *	1441	** 116%
<b>H110</b>	20.5 * MAX.	1580	** 118%
	20.0	1559	** 115%
	19.5	1537	** 112%

All cartridge measurements are SAAMI maximum and due to variations from manufacturers actual measurements may vary

\* Because Nosler, Inc. has no control over the actual components selected, the manner in which they are assembled or the condition of the firearm used, no responsibility, either expressed or implied is assumed for the use of this data.

In no event shall Nosler, Inc. be liable for any damages resulting from the use of this data.\*

\* = Most accurate load tested

\*\* = Compressed load