


CARTRIDGE

8x57 JS Mauser - 180 grain

Version 8.0

Nosler®

UP FRONT



8x57 JS Mauser - 180 grain

8mm (.323")

MAXIMUM S.A.A.M.I. O.A.C.L. 3.250"

TESTED O.A.C.L.

B.C.

S.D.

| | | | | |
|--|----------------|--------------------|-----------|-------|
| Ballistic Tip® | 180gr. Spitzer | 3.030" | 0.394 | 0.246 |
| E-Tip® | 180gr. Spitzer | 3.030" | 0.427 | 0.246 |
| Due to internal construction differences, always begin with starting loads when using E-Tip® products. | | | | |
| CASE TYPE: | Federal | PRIMER TYPE | WLR | |
| CASE HOLDS: | 52.4 Gr. WATER | BARREL Length/Make | 24" Lilja | |
| | | BARREL Twist | 1-10" | |

| POWDER TYPE | POWDER CHG. GRS. | MUZZLE VEL. F.P.S. | LOAD DENSITY (VOLUME) |
|--|------------------|--------------------|-----------------------|
| Viht N140 | 46.0 MAX. | 2541 | ** 102% |
| | 44.0 * | 2444 | 98% |
| | 42.0 | 2334 | 93% |
| IMR 4350 | 52.0 MAX. | 2545 | ** 105% |
| | 50.0 | 2494 | ** 101% |
| | 48.0 * | 2403 | 97% |
| IMR 4064 Most Accurate Powder Tested | 47.0 MAX. | 2636 | 99% |
| | 45.0 | 2532 | 94% |
| | 43.0 * | 2410 | 90% |
| RL15 | 48.5 MAX. | 2667 | 96% |
| | 46.5 | 2576 | 92% |
| | 44.5 * | 2462 | 88% |
| Varget | 49.0 MAX. | 2669 | ** 101% |
| | 47.0 | 2567 | 97% |
| | 45.0 * | 2464 | 93% |

All cartridge measurements are SAAMI maximum and due to variations from manufacturers actual measurements may vary

* Because Nosler, Inc. has no control over the actual components selected, the manner in which they are assembled or the condition of the firearm used, no responsibility, either expressed or implied is assumed for the use of this data.

In no event shall Nosler, Inc. be liable for any damages resulting from the use of this data.*

* = Most accurate load tested

** = Compressed load